

PARTNER

CARE . TRUST . RESPONSIBILITY

Cash Drawer Key Features

- Secure and Durable
- 4 note and 8 coin insert included
- Media slot



Customer Display Key Features

- Easy to read characters and graphics
- User Friendly
- Variety of Interfaces
- Adjustable height



Peripherals
Completing the
Partner Tech
hardware solution

Partner Tech UK Corporation
www.partnertech-uk.com

Peripherals: Completing the Partner Tech hardware solution

With Partner Tech's range of versatile peripherals you can easily complete your POS solution. The cash drawers are hard wearing and functional in design with secure locks. The customer displays can optionally draw power from a host POS system, making it independent of a separate power supply unit. Available in black and cool white with adjustable height, the customer display units can be matched to the requirements of any working environment.

5E-415	
Construction	All Steel
Rails	Roller Bearing
Media Slot	2 Media Slots
Insert	4 note/ 8 coin adjustable sections
Lock	3 positions
Micro Switch	Yes
Cable Length	0.8M
Interface	Universal printer driven manual/ USB
Solenoid	24V
Dimension	410(W) x 415(D) x 110(H) mm
Weight	6.8kg
Lockable Lid	Options



5E-415



FT-460

FT-460	
Construction	All Steel
Rails	N/A
Media Slot	1 Media Slot
Insert	4 note/ 8 coin adjustable sections
Lock	3 positions
Micro Switch	Yes
Cable Length	0.8M
Interface	Universal printer driven manual/ USB
Solenoid	24V
Dimension	410(W) x 415(D) x 110(H) mm
Weight	4.8Kg
Lockable Lid	Standard

CDU-5220	
Display Method	Vacum Florescent Display
Display Colour	Blue Green
Number of Characters	40 Characters (20 columns x 2 lines)
Brightness	400 cd/m
Character Type	96 alphanumeric 13 international character sets including US, French, German, Spanish, etc
Character Font	5 x 7 dot matrix, comma and decimal point
Character Size	9.0 mm x 5.25mm
Character Pitch	8.3mm
Interface	Serial/ Parallel/ Pass Through (option)
Power Supply Voltage	DC 12V (+5/-5%)
Power Consumption	3W
MTBF	25,000 hours
View Angle	8-45 degree
Dimensions (Head)	226 (W) x 92 (H) x 50 (D) mm
Certification	FCC, CE, BSMI

	CDU-7220	CDU-7220D	CDU-7220-UN 5V	CDU-7220-UN-D 5V
Display Method	Vacum Florescent Display			
Number of Characters	40 Characters (20 columns x 2 lines)	80 Characters (20 columns x 2 lines)	40 Characters (20 columns x 2 lines)	80 Characters (20 columns x 2 lines)
Display Colour	Blue Green			
Brightness	400 cd/ m		350 cd/ m	
Character Type	96 alphanumeric 13 international character sets including US, French, German, Spanish, etc			
Character Font	5 x 7 dot matrix, comma and decimal point			
Character Size	9.0 mm x 5.25mm			
Driver	OPOS		Windows XP & Vista (WHQL/WLK certified) OPOS	
MTBF	25,000 hours			
Power Supply	External Adaptor, 12V/1A		W/o external power adaptor, get USB 5V directly	
Rotation Angle	maximum 270 degrees			
Interface	RS232 (Option: Pass Through)		USB 2.0	
View Angle	-20-20 degree			
Power Consumption	3W	5W	2W	3.5W
Dimensions (Head)	230 (W) x 80 (H) x 40 (D) mm			
Certification	FCC class B, CE class B, BSMI			



CDU-5220



Partner Tech Corporation

UK
T: +44 (0) 1928 579 707
F: +44 (0) 1928 571 308
E: sales@partnertech-uk.com

Taiwan
T: +886 2 291 88500
F: +886 2 291 53405
E: sales@partner.com.tw

USA
T: +1 949 598 1888
F: +1 949 598 0088
E: sales@partnertechcorp.com

Europe
T: +49 (0)40 450 635 0
F: +49 (0)40 450 635 130
E: info@partner-tech.eu

China
T: +86 21 676 9 6667
F: +86 21 676 9 669
E: sales@partnertech.com.cn